

**AMP-30D Dry-mixed Motar Sparying Machine**



**AMP-30D Dry-mixed Motar Sparying Machine Description:**

AMP-30D is a continuously working mixing machine, designed for the application of any type pumpable dry ready-mixed mortar based on cement, gypsum and insulating mortar.

In the European and other developed countries, this type machine has been universally using with its reliability and stability in performance.

The machine consists of portable units, permitting easy and comfortable transport due to their small and handy dimensions and low weights.

Thanks to its efficiency, silence and technical perfection, AMP-30D is the top-priority machine for dry ready-mixed mortar.

**AMP-30D Dry-mixed Motar Sparying Machine Features:**

- Integrated machine with mixer, self-suck water pump, mini compressor and rotor/stator pump
- The continuously mixing and pumping machine
- Small and handy dimension and low weight, quickly and easily transport even in the most confined spaces. The rotor/stator pump ensures the material is pumped and sprayed out continuously and evenly.
- The machine always works with efficiency and silence

**AMP-30D Dry-mixed Motar Sparying Machine Technical Data**

Output	30 L/min
Rated Working Pressure	3 Mpa
Total Power	8.5 Kw
Main Electric Motor	3 Phase, 380 volt, 5.5 Kw
Rev.of Rotor	380 RPM
Rated Air Output	250 L/min



Water Pump Rated Output	700 L/h
Max.Conveying Dist.	50 m
Hopper Capacity	120 L
Loading Height	1000 mm
Conveying Hose ID.	25/32 mm
Air Hose ID.	13 mm
Overall Dimension	1240×680×1550 mm
Weight	280 kg

The information contained in this document is believed to correct but A.E.G(Wuxi) Machinery Co., Limited accepts no liability for any errors it contains, and reserves the right to alter specifications without notice. Please consult the respective machine manual for all matters related to operations and maintenance.