

**AMT300-750 Double-layer Grout Mixer**



**AMT300-750 Double-layer Grout Mixer Introduction:**

AMT300-750 Grout Mixer mainly mix cement grout and similar slurry. Combine with grouting pump, it can grout with pressure in mining, tunnel, culvert, subway, hydropower engineering, underground excavation engineering etc.

**AMT300-750 Double-layer Grout Mixer Advantages:**

- AMT300-750 is composed of base, governor motor shaft
- Material barrel is driven by the positive shaft to make complex movement including horizontal move, rotation and rolling etc., which makes the material move in 3 directions along the barrel, therefore, highly uniform mixing of various material is realized
- It has larger loading capacity, short mixing time and high efficiency.

**AMT300-750 Double-layer Grout Mixer Technical Data Sheet**

Mixing tank capacity	300 L
Agitating tank capacity	750 L
Mixing speed	550 r/min
Agitating speed	33 r/min
Mixing Unit	4 kW
Agitating Unit	1.5 kW
Chassis	kickstand
Dimensions	1698×1118×1600 mm
Weight	500 kg
Application field	Grout or other materials suitable for being mixed quickly

The information contained in this document is believed to correct but A.E.G(Wuxi) Machinery Co., Limited accepts no liability for any errors it contains, and reserves the right to alter specifications without notice. Please consult the respective machine manual for all matters related to operations and maintenance.